



Technical Information

WHISPER 60 modular 12/24V/ 230V

Utilization

Production



Whisper 60 modular

Desalination System for Sea Water, Brackish Water and cleaning of Fresh Water

SEA STAR WHISPER 60 = **60** Liter/h +/-10% (Depends on Sea Water Temperature and Salinity) 35000 ppm.*

The heart of the system is the **ETD** (Energy Transfer Device) The ETD produces out of large volume water with low pressure, High pressure, with a low volume of water. The built in Energy recovery circuit pushes the ETD and saves energy by using the concentrate back flow.

The advantage of this system is:

The system produces almost no noise.

No high pressure regulation is needed, the system regulates by itself.

It is a switch On/Off system.

New ceramic parts extend the time between overhaul. More Water is pumped through the membrane which extends membrane life and increases water quality.

*ppm (parts per million TDS= Total dissolved solids.





Membrane

TFC (Thin film composite) Membrane, WHISPER 60 = 1 x 2540

Pre-Filter

Connection sizes

Concentrate Flow

Weight

Water Quality

Delivery

Warranty

Extras

Voltage

Pre-Filter 5µ with expansion Tank

1/2" hose connection. Feed Pump must be at or below the waterline

1/2" hose connection. Outlet must be over the Waterline.

Either 12/24V DC or 230V 50Hz AC WHISPER 60: 29A/14,5A


ca. 45 Kg.


In Sea Water less than 500PPM. Below WHO Standard

Ready to install. Membranes, Pre-Filter, Feed Pump, Freshwater Flush System, ETD, Control Panel. COMFORT Version: With automatic product water control, PH Stabilizer


2 Years on the system, unlimited warranty on the pressure vessel.

Spare Filter, spare Membrane, overhaul kits, preservation Chemicals





ETD



ETD side view

Pressure Vessels



Feed pump







Control panel

Sea Water Filter **Pre-Filter** Carbon Filter

PureWater Entsalzungsanlagen

Bodelschwinghstraße 37 | 33142 Büren Germany Büro Düsseldorf +49(0)211.29 36 944 Fax +49(0)211.29 36 945 Lager +49(0) 295.5 14 16 | Mobil +49(0) 171.3 84 60 92 Mail purewater@watermaker.de | Internet www.watermaker.de